



PRODUCT DATA SHEET

Mountain Protective Coatings PEAK LT Priming Paste is a proprietary substrate primer that displaces moisture, pacifies oxides, and fills small irregularities prior to wrapping with the PEAK LT Petrolatum Wax Tape system.

PEAK LT PRIMING PASTE

WAX TAPE SYSTEM



FEATURES & BENEFITS



- ✓ **SIMPLE SINGLE COMPONENT COMPOUND**
Easy to apply and requires no mixing or ratio measurements.
- ✓ **PROTECTS SUBSTRATE**
Resistant to water, acids, and salts.
- ✓ **FLEXIBLE APPLICATION**
Can be applied underwater and to wet, dry and sweating assets.
- ✓ **EFFICIENT PREPARATION**
Minimal surface preparation SSPC SP2 – SP3.
- ✓ **INDUSTRY CERTIFIED**
Meets AWWA C217 & CSA Z245.30 system FC7 requirements.



+1-604-787-4085

info@mountain-pc.com

www.mountain-pc.com





PEAK SYSTEM

- ✓ MPC PEAK LT Petrolatum Wax Tape
- ✓ MPC PEAK LT Priming Paste
- ✓ MPC PEAK LT Profiling Mastic
- ✓ PEAK / CNRI® SynthoGlass® OUTERWRAP
- ✓ ACCESSORIES: Compression film, perforator

APPLICATIONS

- ✓ Above and below ground assets
- ✓ Valves, fittings, flanges and risers
- ✓ Soil to air transitions
- ✓ Rehab tie-ins
- ✓ Emergency repair
- ✓ Underwater and splash zones



PHYSICAL PROPERTIES

PROPERTY	SPECIFICATION
FLASH POINT	265°C (510°F)
SPECIFIC GRAVITY @ 25°C	1.03
CONE PENETRATION @ 25°C	12.5mm (0.5 in.)
DROP MELTING POINT	60°C (140°F)
PETROLATUM WAX BY WEIGHT	77%
MINIMUM SERVICE TEMPERATURE	-40°C (-40°F)
MAXIMUM SERVICE TEMPERATURE	50°C (122°F)
MAXIMUM APPLICATION TEMPERATURE	-40°C (-40°F)

PAIL SIZE	PAILS PER CASE	TOTAL CASE WEIGHT
2kg (4.4lb)	6	12kg (26.5lb)
4kg (8.8lb)	4	16kg (35.2lb)

SIZE & QUANTITY

ORDER PRODUCT

info@mountain-pc.com

